

Fully Rugged



Highly productive with powerful features
 The SOUTH X11 comes with Windows Embedded Handh

The SOUTH X11 comes with Windows Embedded Handheld 6.5, 1 GHz processor and advanced manufacturing process, which can drive any filed software with easy and provide customers with a wider range of uses and application.

Built to survive

With rugged and reliable design, in addition to IP67 certification, which can protect it well during work in any harsh environment. SOUTH X11 is independently certified to MIL-STD 810G standards including drop from 1.5m and can operate in temperatures from -30°C to 60°C.

Flexible communication and data handling

Stay connected with a wide range of communication and data storage options. With fully integrated wireless technology (Bluetooth, GSM/UMTS 3.5G, WiFi), a choice of two connector modules and data storage using an SD card or external memory stick, The SOUTH X11 are ready for all challenges on site and in the office.

Advanced GIS application

The SOUTH X11 is built with an integrated powerful 72 channels GNSS chip (GPS,GLONASS,BEIDOU,SBAS,QZSS), which can also process RTCM2.3 data from CORS. These features open the door to countless application possibilities, making it ideal for GIS surveying and other GPS/mapping-based applications.



Specifications

X11 (Pro)			
HARDWARE		DATA COMMUNICATION	
Operation system	Windows Mobile6.5	Bluetooth Device	2.1+EDR
Processor	Ti Sitara [™] AM335x 1GHz	WIFI	802.11 b/g/n Wireless LAN
RAM	512MB	Communication module	Built-in universal quad-band communication model (WCDMA
ROM	8GB (Up to 32GB), SD expansion to 32GB	Multi-media	Multimedia message
INTERFACE AND INPUT		Voice Calls	Included
Multi-media	Integrated speakers, microphone, telephone handset, support recording and playback	SIM Card POWER SUPPLY	SIM Card Socket
Soft Key	Digital soft keyboard character input,	Battery Capacity	7.2V, Removable Li-lon 24.4Wh (BP-5S)
	support handwriting and spelling input	Working Hours	Up to 10 hours, Up to 12 hours
External Power Supply	External power connector	PHYSICAL SPECIFICATIONS	
SD Card Slot	Supports SD up to 32GB	Size	193×91×42mm (L*W*D)
USB Port, Serial Port	Yes	Weight	600g (battery included)
DISPLAY		Relative Humidity	5%~95% non-condensing
Model	Blanview TFT, LED Backlighted	Operation Temperature	-30°C~60°C
Resolution	480x680 VGA	Storage Temperature	-30°C~70°C
Size	3. 7inch	Waterproof/ Dustproof	IP67
CAMERA		Shock and vibration	Withstands 1.5m free drop onto hard surface, MIL-STD-810G
Static Model		STANDARD ACCESSORIES	
Image Format		Carton package x 1, Adapter x 1, USB cable x 1, Battery x 1, Handstrip x 1, Stylus & string of	
Video Mode		pen x 1, Screen protector x 1	, Charger set x 1, Bracket x 1
GPS SPECIFICATIONS			
Channels	72		
Tracked Satellites	GPS/QZSS: L1 C/A code SBAS: L1 C/A code WAAS, EGNOS, MSAS GLONASS: L10F GALILEO: E1 B/C		
Accuracy	Velocity accuracy: 0.05 m/s Position accuracy: 2.5m DGPS: Sub meter		
Max navigation Update Rate	4Hz		
Cold Start	29s		
Supported Protocols	Support RTCM 2.3 Differential NMEA 0183 UBX binary, u-blox proprietary		











Add: 7/F, No.39 Si Cheng Road, Tian He IBD Guangzhou 510663, China (South Geoinformation Industrial Park) Tel: +86-20-23380888 Fax: +86-20-23380800 E-mail: mail@southsurvey.com export@southsurvey.com impexp@southsurvey.com gnss@southsurvey.com http://www.southinstrument.com http://www.southsurvey.com